

- 2000 lb capacity evenly distributed
- 16 gauge steel fully welded construction
- Textured baked enamel finish
- Pearl white, IBM blue, black, driftwood grey and any FED-STD-595 color
- Two pair 10-32 tapped angles (mounting rails) per EIA standard-tapped and drilled holes or (cage nuts) square holes
- All mounting holes attach any exterior option
- ISO 9001 approved facility for manufacture of electrical enclosures

Dimensions

- Width: 19, 23, 24 and 48" rack mount
- Height: 45.5, 70 and 77" vertical rack mount
- Depth: 24, 30, 36, 40 and 42"
- Custom dimensions are available through quotations

Door-Front/Back

- Front aluminum frame smoked Plexiglas doors w/ lock
- Front steel frame smoked tempered glass doors w/ lock
- Vented steel frame tempered glass doors w/ lock
- Full-length rear doors available as solid, bottom louvered, fully louvered, and perforated w/ lock

Side Panel

- Removable swing out side panels, solid or mesh w/ lock

Top Panel

- Removable top panels available in solid, vented, louvered, mesh or with holes for 1 or 2 fans with (4) 3.5" cutouts for cable access with grommets and plugs

Shelving

- Stationary shelves available for all your configurations
- Sliding shelves available for any need
- Pullout drawers in many sizes and styles
- Standard shelves-static load of 250 lb
- Heavy duty shelves-static load of 600 lb
- Rotating and standard keyboard shelves
- 16 gauge steel-textured baked enamel, available in all cabinet colors

Related Accessories

- Power strips in many styles and sizes with or without AMP meter
- Fans for increased airflow
- Aluminum trim packages available
- Casters and levelers are available
- Numbered RMU spaces on the tapped angles (mounting rails) are an option

